



Bona Gel



Bona Gel

Gel is a waterborne thixotropic primer designed for trowel application on wooden floors exposed to normal wear. Easy application and very quick drying makes it possible to get the floor finished and ready in only one day. If used between coats it cleans the surface of fine dust and fills minor joints/scratches, improving both the filling ability and the appearance of the floor.



Key Benefits

- Waterborne PU/acrylate co-polymer
- Designed for use with all Bona waterborne top coats
- Makes a fast system possible
- Gives a well-bodied surface
- Additional filling of the joints
- Minimizes the risk of sidebonding
- Abrading normally not required

Technical Data

Type of finish:	1-comp. waterborne PU/acrylate co-polymer
Solids content:	Approx. 40%
Drying time:	10–15 minutes at 20°C / 60% R.H.
Application tools:	Stainless steel trowel
Application rate:	
As primer:	1 litre / 25–35 m ² per coat, depending on type of wood
Between coats:	1 litre / 50–100 m ² per coat
Safety:	Unclassified
Flash point:	Non-flammable
Shelf life:	At least 1 year, from the date of production, in unopened original container
Storage / transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport
Pack size:	1 x 5 litres (60 boxes per pallet) 6 x 1 litre (486 boxes per pallet)