



Bona Novia



Bona Novia

Bona Novia is a one-component waterborne finish for the surface treatment of wooden floors in domestic areas and other areas subject to normal – heavy wear.

Bona Novia can be combined with any Bona waterborne primer but also works well applied directly to wood and brings out a warm colouration to many timbers.



Key Benefits

- Easy to use, no primer needed
- Self-crosslinking, acts as a 2-component product but without requiring any mixing
- Good resistance to wear, chemicals and scuff marks
- Non-yellowing
- Quick drying

Technical Data

Type of finish:	1-component waterborne dispersion.
Solids content:	Approx. 30%
Solvent content:	Max 60 g/l VOC.
Viscosity:	Approx. 20 sec. (25°C, FC4)
Resistance to wear:	Approx. 8 mg/100 revolutions (SIS 923509)
Sheen (at 60°):	Gloss: 85, SilkMatt: 45, Matt: 25 (approx. values)
Drying time:	1–2 hours at 20°C/60% R.H.
Application tools:	Bona Roller or Bona Applicator
Application rate:	8–10 m ² /litre (120–100g/m ²) per coat
Safety:	Unclassified, see safety data sheet for more information.
Shelf life:	1 year from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport. Reseal the container directly after use.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations. Do not allow to enter drains or watercourses.
Pack size:	2 x 10 litres (24 boxes per pallet) 3 x 5 litres (44 boxes per pallet) 10 x 1 litre (50 boxes per pallet)