



Bona Oil 90



Bona Oil 90

Bona Oil 90 is a hardening tall oil containing less than 10% solvents which is intended for the surface treatment of untreated wooden floors exposed to normal or heavy wear. Due to its easy application and quick drying, the floor may be completed within one working day.



Key Benefits

- Based on tall oil from pine trees
- Dry solids 90%
- Easy to apply
- Dries quickly
- Ready in a day
- Practically no bleed-back
- Excellent coverage rate
- Meets RAL-UZ 38 for VOC and formaldehyde emissions
- Meets DIN EN 71/3 for use on children's toys

Technical Data

Type of oil:	Esterified tall oil
Solids content:	Approx. 90 %
Density:	0.92 kg/dm ³
Dilution:	Do not dilute
Waiting time between applications:	Approx. 20 minutes
Application tool:	Solvent-resistant rubber applicator
Total consumption:	Approx. 10–12 m ² /litre depending on type of wood
Safety:	Unclassified
Fire risk:	Yes (see the Safety Data Sheet)
Flash point:	56°C
Shelf life:	At least 2 years, from the date of pro- duction, in unopened original container
Storage:	Store frost-free
Pack size:	2 x 5 litres (35 boxes per pallet) 6 x 1 litre (72 boxes per pallet)