

SAFETY DATA SHEET

Bona Sportive Paint, various colours

1. Identification of the preparation and of the company

Product name and/or code : Bona Sportive Paint, various colours**Synonyms** : WC4101-WC4901**Manufacturer** : Bona AB
Box 210 74
SE-200 21 MALMÖ
SWEDEN
Tel. +46-(0)40-38 55 00**e-mail address of person responsible for this SDS** : marie.holmgren@bona.com**Product use** : Line-marking paint for wooden floors

2. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Not classified.**Additional warning phrases** : Safety Data Sheet available for professional user on request.

3. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS number	%	EC number	Classification
2-Methyl-2,4-pentanediol	107-41-5	1 - 2.5	203-489-0	Xi; R36/38 [1] [2]
See section 16 for the full text of the R-phrases declared above				

There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

4. First aid measures

First aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

6. Accidental release measures

- Personal precautions** : Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Keep container tightly closed.
- Avoid contact with skin and eyes. Avoid inhalation of vapor, spray or mist.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.
- Keep away from: oxidizing agents, strong alkalis, strong acids.
No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Do not empty into drains.

8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Ingredient name

2-Methyl-2,4-pentanediol

Occupational exposure limits

ACGIH TLV (United States, 2007).
CEIL: 25 ppm

Personal protective equipment

- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

8. Exposure controls/personal protection

Hands

Gloves : For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Eyes : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. Physical and chemical properties

Physical state : Liquid.

Color : Black. Blue. Green. Orange. Red. White. Yellow.

Relative density : 1 to 1,3

Solubility : Soluble in the following materials: cold water and hot water.

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Methyl-2,4-pentanediol	LD50 Dermal	Rabbit	13300 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Aquatic ecotoxicity

<u>Product/ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Species</u>	<u>Exposure</u>
2-Methyl-2,4-pentanediol	-	Acute EC50 3200 mg/l	Daphnia	48 hours
	-	Acute EC50 >1000 mg/l	Daphnia	48 hours
	-	Acute IC50 >429 mg/l	Algae	72 hours
	-	Acute IC50 >429 mg/l	Algae	72 hours
	-	Acute LC50 >1000 mg/l	Fish	96 hours
	-	Acute LC50 12800 mg/l	Fish	96 hours
	-	Acute LC50 8510 mg/l	Fish	96 hours

Conclusion/Summary : Not available.

Ecological information

Biodegradability

Conclusion/Summary : Not available.

Bioaccumulative potential

<u>Product/ingredient name</u>	<u>LogP_{ow}</u>	<u>BCF</u>	<u>Potential</u>
2-Methyl-2,4-pentanediol	-0.14	-	low

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

European waste catalogue (EWC) : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 12 waste paint and varnish other than those mentioned in 08 01 11. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

Hazardous waste : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

14. Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Sea

Special provisions : Not available.

Marine pollutant : No.

Air

Special provisions : Not available.

The "viscosity exemption" provisions do not apply to air transport.

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

15. Regulatory information

EU regulations	: The product is determined as not being dangerous according to the requirements of the DPD.
Risk phrases	: This product is not classified according to EU legislation.
VOC for Ready-for-Use Mixture	: IIA/i. One-pack performance coatings. EU limit values: 140g/l (2007) 140g/l (2010.) This product contains a maximum of 100 g/l VOC.
Europe inventory	: Europe inventory: Not determined.
Additional warning phrases	: Safety Data Sheet available for professional user on request.

16. Other information

CEPE Classification	: 8
Full text of R-phrases referred to in sections 2 and 3 - Europe	: R36/38- Irritating to eyes and skin.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

Date of issue/Date of revision : 2009-12-01.

Version : 1

✔ Indicates information that has changed from previously issued version.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.