



# Bona H600



# Bona H600

H600 is a cementitious, self-smoothing, rapid hardening levelling compound especially for the application under mosaic parquet, lamparquet, multi-layer parquet and solid parquet. Only for interior use.



## Key Benefits

- Self levelling
- Self smoothing
- High strength and hardness
- Low shrinkage
- Low tension
- Could be covered after 24 hours
- Applicable in a thickness from 1,5 to 10 mm, for bigger thickness the material could be spun out
- Cement-based
- Levelling compound
- Smoothing compound
- Self-smoothing
- Polishable
- High filling properties
- Pumpable
- Crack-free
- Makes surfaces ready to receive floor coverings in one single operatio

## Technical Data

Base:	Cement
Color:	Grey
Consumption:	1.5 kg per m <sup>2</sup> and mm
Pot life:	30 min
First load (walking):	After approx. 3 hours
Covering:	After approx. 24 hours (1,5-10mm) After approx. 48 hours (10-20mm)
GISCODE:	ZP1
Ecode:	EC1R
Cleaning agent:	Water (only for fresh product!)
Storage:	Not below +5 °C during Winter, below +30 °C in Summer
Shelf life:	12 months
Pack Size:	25 kg paper sacks (40 per pallet)

Additional detailed information is noted in the appropriate Safety Data Sheet.