



Bona R580



Bona R580

R580 is a solvent and water free silane based compound for priming substrates, special for damp-proofing cementitious screeds and concrete floors with moisture up to 5 CM% or 90 % rel. air humidity. It can be used as a 1-Component or 2-Component material. It is used before using R850, R850T or levelling compounds. While the adhesives are applied direct on the primer, levelling compounds need a broadcasting of sand in the wet primer. Remark: Bona R840, R845 and R860 are also compatible with the primer, but have a higher water permeability.



Key Benefits

- Can be used as a 1-Component system or a quicker hardening 2-Component system, with water (added to the 6 kg package in a little bag) as hardener
- Quick and easy application with a trowel, other tools are possible
- Rapid setting
- Not hazardous, safe handling and transport without constraints
- EC1R Plus certified

Technical Data

Product type:	Silane based
Colour:	White
Viscosity:	Easy to apply – self levelling
Density:	1,25 g/cm ³
Cleaning agents:	S100, acetone, ethanol, white spirit. Set material can only be removed mechanical.
Storage / transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport. Store in a dry, well ventilated place.
Shelf life:	6 months. If the product has settled out after longer storage times, stir thoroughly prior to use.
Pack size:	One component - net 7 kg per bucket (60 per pallet) Two component - net 6 kg per bucket (60 per pallet) including a bag with water (60 gram), to be used as a 2nd component.