

# Bona Belt

## Technical data sheet

The compact design makes the Bona Belt simple to manoeuvre and the specially designed transport cart makes the machine easy to transport in between jobs. Powerful and effective, with two optional drum widths, 200 and 250 mm, makes it a versatile belt machine for many purposes. The machine can be disassembled and reassembled quickly and easily. The easy-start function ensures reliable start-up under all conditions. The Bona Belt has a very efficient vacuum that minimises dust. For optimal dust reduction, the Bona Belt is compatible with Bona DCS 70 (Bona Dust Containment System).

### Application

For sanding all kinds of wooden and parquet floors.

### Key Benefits

- Adaptive to many needs
- Compact design makes the machine simple to manoeuvre and easy to transport
- Unique construction with a simple change of drums with either a 200 mm or a 250 mm width
- Ergonomically designed feather handle for raising and lowering of drum
- Very efficient vacuuming
- Adjustments can be made from top of machine
- Large front and side covers make the drum and tension roller easy to reach
- Transport cart for easy transportation between sites
- Dust containment ready

### Technical data

Drum width:	200 mm alt. 250 mm
Sanding belt size:	200 x 750 mm alt. 250 x 750 mm
Easy start:	Enables 1-push start on a 10 A fuse
Motor power:	1-phase 2.2 KW
Total weight:	74 kg
Dust discharge:	< 2 mg / m <sup>3</sup> air

Sanding



**Bona**<sup>®</sup>