



# Bona R844



# Bona R844

R844 is a one-component, silane-based, 'soft elastic' (according to EN 14293) adhesive for dimensional stable multilayered, engineered parquet. Tensions to the sub floor are reduced. Use of a primer is in general not necessary. The adhesive hardens by a chemical reaction with moisture.



## Key Benefits

- 1-component, easy to handle
- Soft elastic
- Water and solvent free, nearly no swelling of the wood
- Good adhesion to almost all substrates and timber materials, splashed material can be easily removed
- Firm texture – retains trowel pattern
- Rapid initial bonding strength

## Technical Data

|                      |   |
|----------------------|---|
| Base:                | Silane modified-Prepolymere   |
| Colour:              | Beige   |
| Viscosity:           | Easy to apply - stable  |
| Density:             | 1.60 g/cm <sup>3</sup>  |
| GIS code:            | RS 10   |
| Cleaning agents:     | Bona S100, acetone and ethanol.<br>Hardened adhesive can only be removed mechanically.  |
| Application of load: | 24 to 48 h  |
| Surface treatment:   | Depending on air humidity and the moisture content of the materials between 2 and 4 days  |
| Storage / transport: | The temperature must not fall below +5°C or exceed +25°C during storage and transport. Store in a cool, dry, well ventilated place. |
| Shelf life:          | 6 months.   |
| Pack size:           | 24 kg (32 per pallet) and 15 kg (44 per pallet)   |

Additional detailed information is noted in the appropriate Safety Data Sheet